Breech twistlock

TLA-ANC-BRTL-01 Section 2 — **Container Anchoring / Foundations**



CATEGORY 2
Container Anchoring / Foundations

1 PRODUCT OVERVIEW

Designed for locations where space beside the container is limited (e.g. container already placed adjacent). Available in left or right locking configuration. Must be used in conjunction with a matching Breech base deck socket or deck recess.



2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	**TLA-ANC-BRTL-01**
Material	Heat Treatable Steel
Load Rating	MBL: 500 kN tension / 420 kN shear / 2000 kN compression
Finish	Hot Dip Galvanised
Applicable Standard	*On application*
Unit Weight	5.5 kg

DRAFT

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	MBL: 500 kN tension / 420 kN shear / 2000 kN compression

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	*On application*
Unit Weight	5.5 kg

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	Heat Treatable Steel
Finish / Coating	Hot Dip Galvanised
Applicable Standards	*On application*
Compatibility / Fitment	*On application*
Country of Origin	*On application*

6 APPLICATIONS

- Space-constrained container securing (containers placed directly adjacent)
- marine and shore stacking applications

7 SAFETY NOTICES

⚠ **SAFETY**

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION

This datasheet	DRAFT A · 2026-08-20 — verify current issue online
2D dimensioned drawing	On request — verify availability online
3D model (STEP)	In production — check availability online

Scan the QR code or visit twistlockafrica.co.za/go/tla-anc-brtl-01 to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)