
Deck socket - flush (double, longitudinal)

TLA-ANC-DSKF-DL

Section 2 — **Container Anchoring / Foundations**



CATEGORY 2
Container Anchoring / Foundations

1 PRODUCT OVERVIEW

Welded flush into tweendecks. Single, double and quad configurations. Standard top-plate thickness 16mm or 28mm depending on tank-top thickness. Standard diameter 205mm (single). Standard pitches: 203/365/258mm (others on request). Weldable inorganic zinc or shop primer. High tensile steel. Tightness tested.

[PHOTO REQUIRED — Deck socket - flush (double, longitudinal): hero shot, 3/4 angle on neutral background]

2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	**TLA-ANC-DSKF-DL**
Material	High Tensile steel; weldable inorganic zinc or shop primer
Load Rating	SWL 210 kN shear / 250 kN tension
Finish	*On application*
Applicable Standard	DNV-GL classification society approval
Unit Weight	*On application*

DRAFT

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	SWL 210 kN shear / 250 kN tension; BL 420/500 kN

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	Top plate Ø205mm (single), thickness 16 or 28mm; standard pitches 203/365/258mm
Unit Weight	*On application*

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	High Tensile steel; weldable inorganic zinc or shop primer
Finish / Coating	*On application*
Applicable Standards	DNV-GL classification society approval
Compatibility / Fitment	*On application*
Country of Origin	*On application*

6 APPLICATIONS

- Tweendeck container securing
- naval and commercial shipping applications

7 SAFETY NOTICES

⚠ **SAFETY**

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION

This datasheet	DRAFT A · 2026-08-20 — verify current issue online
2D dimensioned drawing	On request — verify availability online
3D model (STEP)	In production — check availability online

Scan the QR code or visit twistlockafrica.co.za/go/tla-anc-dskf-dl to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)