Deck socket - raised (single, H=110)

TLA-ANC-DSKR-110S Section 2 — **Container Anchoring / Foundations**



CATEGORY 2
Container Anchoring / Foundations

1 PRODUCT OVERVIEW

Single, double side-by-side and double transverse configurations. Other heights available on request. High tensile steel.



2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	**TLA-ANC-DSKR-110S**
Material	Blank steel
Load Rating	SWL 210 kN shear / 250 kN tension
Finish	Primed
Applicable Standard	*On application*
Unit Weight	6 kg

DRAFT

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	SWL 210 kN shear / 250 kN tension; BL 420/500 kN

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	160 × 160 × 110
Unit Weight	6 kg

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	Blank steel
Finish / Coating	Primed
Applicable Standards	*On application*
Compatibility / Fitment	*On application*
Country of Origin	*On application*

6 APPLICATIONS

- Container stacking — counterpart to manual, semi-automatic and turnfoot twistlocks
- ship decks, stacking yards

7 SAFETY NOTICES

⚠ **SAFETY**

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION

This datasheet	DRAFT A · 2026-08-20 — verify current issue online
2D dimensioned drawing	On request — verify availability online
3D model (STEP)	In production — check availability online

Scan the QR code or visit twistlockafrica.co.za/go/tla-anc-dskr-110s to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)