Lifting lugs - side entry

TLA-LFT-LLSE-01 Section 6 — **Container Adjusting / Lifting**



CATEGORY 6
Container Adjusting / Lifting

1 PRODUCT OVERVIEW

Well-established industry standard. Insert into side hole of bottom corner casting — 2 left-hand and 2 right-hand per set, pointed towards each other when correctly installed. As certified lifting equipment, must not be dropped on hard surfaces. Use only for intended container lifting purpose.

[PHOTO REQUIRED — Lifting lugs - side entry: hero shot, 3/4 angle on neutral background]

2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	**TLA-LFT-LLSE-01**
Material	Cast steel
Load Rating	SWL: 12.5 tons per lug
Finish	Powder-coated Yellow
Applicable Standard	*On application*
Unit Weight	4 kg per lug; lifting hole diameter 70mm

DRAFT

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	SWL: 12.5 tons per lug

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	*On application*
Unit Weight	4 kg per lug; lifting hole diameter 70mm

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	Cast steel
Finish / Coating	Powder-coated Yellow
Applicable Standards	*On application*
Compatibility / Fitment	*On application*
Country of Origin	*On application*

6 APPLICATIONS

- Container lifting with cranes using bottom corner castings
- set of 4 (2 LH + 2 RH) required
- shackle required to connect to lashing equipment

7 SAFETY NOTICES

⚠ **SAFETY**

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION

This datasheet	DRAFT A · 2026-08-20 — verify current issue online
2D dimensioned drawing	Included in this document (page 3) — verify latest revision online
3D model (STEP)	In production — check availability online

Scan the QR code or visit twistlockafrica.co.za/go/tla-lft-llse-01 to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)

9 DIMENSIONED DRAWING / PRODUCT SHEET — CONTAINER LIFTING LUGS REV 0


Tusker® Container Lifting Systems

Container Lifting Systems (supplied in sets of 4. 2 LH/2 RH or 4 straight)

Side Entry Container Lifting Lugs

Model	Product Code	WLL Tonnes Set of 4	Chain Angle		Type	
MKVA	BO 2005094	50	0 - 45° RH/LH		Bottom Lifting	
K:192mm	E:70mm	F:46mm	T:25 mm	G:75mm	H:48mm	Mass 4kg










Top Entry Container Lifting Lugs

Model	WLL kg	Type of lifting	Sling angle from vertical	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
CLT	56000	Top	Vertical	123	217	45	39	57	101	121	28







Address (JHB): 100 8th Avenue, Edenvale, 1610, Gauteng, South Africa
Address (CPT): 17 Simone Street, De Tijger, Parow, 7500, Cape Town, South Africa
Website: www.twistlockafrica.co.za
Email: info@twistlockafrica.co.za
Tel: +27 11 609 7873

TWISTLOCK africa